


| | |
|--------------|------|
| Project Name | Type |
| Catalog # | Date |

UV-C HYBRID TROFFER

UVCT



2x4 Size Shown



APPLICATIONS

- Hospitals
- Educational Facilities
- Clinics
- Office Spaces
- Conference Rooms
- Municipal Facilities
- Financial Institutions
- Hospitality Areas

APPROVALS

- Complies with UL1598 and CSA C22.2#250.0.0:2008
- Suitable for damp locations.
- RoHS Compliant
- BAA Compliant
- ATAL tested www.ata-labs.com

FEATURES

- Single troffer fixture that delivers both UV-C disinfection and White LED light with comfortable, low glare illumination
- Toolless access to plenum
- Indicator light warns when UVC lamp is on

CONSTRUCTION

- Housing is 22 gauge white matte steel
- LED source is indirect
- LED optic is in roll form to provide volumetric appearance
- End caps riveted to housing for strength and rigidity
- Driver & UVC ballast are accessible from plenum
- Frameless lens provides clean appearance.
- Impact resistant, clear polycarbonate covers LED modules

UVC

- 254 nm wavelength
- Irradiance: .06 mJ/cm² @ 8 ft
- Produces no ozone or other secondary contaminants

ELECTRICAL

- Voltage: 120V AC input
- LED Driver: 24VDC Class 2, constant current, electronic power supply factory calibrated to LED modules. 120V with 0-10V dimming as standard on LEDs
- Best In Class LEDs: 3000K, 3500K, and 4000K, CCT (min 80 CRI)
- Occupancy sensor lighting control with both PIR and ultrasonic sensors up to 1000 sq ft

ACCESSORIES

- Recessed troffer flange kit available, ordered separately (consult factory)
- Wire Guard over UVC lamps

WARRANTY

- Fixture backed by XtraLight's UV warranty

ORDER LOGIC

SAMPLE CATALOG NUMBER: UVCT24-4000L- 1FT-40K-DIM-SCP-WG

| UVCT | | - | | - | | - | | - | | - | SCP | - | |
|------|--------|---|-------|---|-------------------|---|-----------|---|---------------------------------------|---|--------------------------------|---|--|
| | SIZE | | MODEL | | UVC LAMP | | CCT | | DRIVER | | LENS | | OPTIONS |
| | 22 2x2 | | 4000L | | 1 ft ² | | 30K 3000K | | DIM ³ Dimmable 0-10V, 120V | | SCP Smooth Clear Polycarbonate | | EM Emergency Battery Back-Up |
| | 24 2x4 | | 5000L | | 2 ft ¹ | | 35K 3500K | | | | | | GTD ¹ Generator Transfer Device |
| | | | 7000L | | | | 40K 4000K | | | | | | WG UVC wireguard |


1. Only Available For 2x4 Fixture
2. Only Available For 2x2 Fixture
3. LEDs Only

UV-C HYBRID TROFFER

UVCT

DIMENSIONAL DATA

2X2 SIZES SHOWN



2X4 SIZES SHOWN

