

PROJECT INFORMATION

Project Name

Туре

Catalog #

Date

UV-C HIGH POWER DISINFECTION SYSTEM SURFACE

UVC SURF PRELIMINARY SPEC SHEET

> Wireguard as shown is optional





APPLICATIONS

- Elevators
- Classrooms
- Offices
- Any other unoccupied space

APPROVALS

- Complies with UL 153 and CSAC22.2#250.4
- RoHS Compliant
- BAA Compliant
- ATAL tested <u>www.ata-labs.com</u>

CORNER MOUNT

FEATURES

- Surface mounted fixture delivers high power UVC disinfection when space is unoccupied
- Sensor switches power to lamp in the off position when occupancy is detected
- Optional tamper proof fasteners prevent access to components other than authorized servicing
- Uses one or two quartz glass germicidal UVC lamp(s) with ceramic caps
- Easy UVC lamp change out

UVC

- 254 nm wavelength
- Irradiance: .2 mJ/cm²@5 ft
- Produces no ozone or other secondary contaminants

ELECTRICAL

• 40W-80W

- Voltage: 120-277VAC input 50/60 Hz
- FCC compliant with Part 15 Class A

CONSTRUCTION

- Custom fabricated wire guard post powder painted white after forming
- 20 gauge steel housing, post powder painted white
- Quartz glass germicidal UVC lamps with ceramic end caps and G13 sockets
- Wall or Ceiling mounted sensors
- 95% reflective optic


LAMP REPLACEMENT

- For optimum results, replace UVC lamps after 9,000 hours or one year of operation
- Contact factory for lamp replacement and pricing

WARRANTY

Unit backed by XtraLight's UV warranty

ORDER LOGIC



SAMPLE CATALOG NUMBER: UVCS4-CN-2L-WG

WARNING: To guard against damage observe basic safety precautions including: Wear protective gear when operating and handling the unit including: goggles, gloves, and faceshields. Read and follow all instructions, warnings, and safety notices instructions. Do not expose eyes and skin to direct or reflected UVC rays as they are harmful.




itions including: Wear protective

UV-C HIGH POWER DISINFECTION SYSTEM SURFACE

UVC SURF

DIMENSIONAL DATA





WORKING HARDER. LIGHTING SMARTER."

<u>www.XLM.com</u> • (800) 678-6960 • <u>customerservice@XLM.com</u> All information is believed to be accurate at the time of publication. Please contact customer service or visit www.XLM.com for the most updated product specifications. XtraLight® reserves the right to change specifications without notice.